R Flashings

Res EDPM with Aluminium Base (with built in 20° Pitch)



Res 1. Code LFRES1 100mm (4") – 200mm (8") Base. 508mm x 609mm Res 2. Code LFRES2 175mm (7") – 275mm (11") Base. 660mm x 762mm

Res EDPM with Safe Lead Base (with built in 20° Pitch)



Res 1. Code RES1LEAD 100mm (4") – 200mm (8") Base. 508mm x 609mm Res 2. Code RES2LEAD 175mm (7") – 275mm (11") Base. 660mm x 762mm

Vertical EDPM Safe Lead Base (Flat)



Code TFLDVB 175mm (7") – 330mm (12") Base, 535mm x 835mm

EDPM Screw Down



Code 301. 0mm – 146mm
Base. 203mm / 8" square
Code 601. 120mm – 254mm
Base. 305mm / 12" square
Code 801. 170mm – 340mm
Base. 430mm / 17" square

Lead



190mm (7.5"), 210mm (8.25") Base 600mm square 235mm (9.25"), 260mm (10.25") Base 750mm square

Pitch. Flat, 20°, 30°, 40°, 50° Others sizes and pitches made to order.

*EDPM suitable for temperature range, - 40°C to 135°C

A FAMILY STOVE
& HEATING BUSINESS. EST. 1974

Castle Farm, Marshfield, Chippenham. Wilts. SN14 8HU www.knight-stoves.co.uk 01225 891469